



Byzantium

Warm tones soft perlescent effects, deep bright and dark light: **BYZANTIUM** is a perfect coat creating a warm and reach atmosphere, where details of the walls act with the interior decoration, creating a unique harmony.

COLOURS: 28 standard colours available by toners or tintosystem.
Gold and silver bases are available.

SURFACE PREPARATION: Smooth surfaces, dry walls need to be primed by one coat of **SAIFSEAL DUR 300%** and two coat of **MICROFINE 500** or **ACRYL 100** white.

APPLICATION: **BYZANTIUM** is ready to use. Apply first coat by fine sponge roller or short hair roller, spreading uniformly the product. Second coat: apply the same way as first coat, let it set for few minute then, by steel spatula, smooth the surface to get the dark-light effect.
Do not over work by spatula, to avoid to kill the perlescent effect.
Clean tools immediately after use, by warm water and soap.



Byzantium

>BYZANTIUM		N B 07
		REV 0
		DEL 17/04/2009
		SPEC. REF. B 07
TECHNICAL DATA		
Binding Agent:	Acryl resin	
Specific weight:	1,17 kg /l \pm 2%	UNI 8910
pH:	8,5÷9,5	UNI 8311
Viscosity Brookfield:	35000 CPS a 20° C. S. 5 RPM $5 \pm 10\%$	UNI 8490
% Solid by weight:	49,5% \pm 2	ISTR 0007
APPLICATION DATA		
Storage temperature	From +10°C to +35°C	
Application Temperature:	From +10°C to +40°C	
Shelf life:	Dry and fresh store, packed and sealed 18 months at least.	
Dilution:	Ready to use	
Drying Time:	2 hours touch dry. Recoatable after 8 hours	
Consumption:	0,15 l/mq for coat	
Packing:	0,750 l - 2,5 l	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility.