



Casanova wax

CASANOVA WAX is a fluid wax for protection of Venetian plaster, based on white spirit.

Can be applied on any smooth. Interior coating: it improves the gloss finish, waterproof the surface, brighten the colours.

COLOUR: uncoloured, when dried.

APPLICATION: can be applied on any substrate, including lime based plasters, well seasoned and clean. Apply one coat of **CASANOVA WAX**, ready to use, by brush or by spray gun.

While drying, spread well by soft cloth or by dry stainless steel spatula. In case of high absorption surface, apply a second coat. Before use, mix well the product.



Casanova wax

> CASANOVA WAX		N C 06
		REV 0
		24/05/2006
		SPEC. REF.
TECHNICAL DATA		
Binding Agent:	Natural wax and paraffin	
Specific weight:	0,8 Kg/ℓ	UNI 8910
Viscosity Brookfield:	1000 CPS ± 2	UNI 8490
% Solid Weight:	13% ± 2%	ISTR 0007
APPLICATION DATA		
Storage temperature	From +10°C to +25°C	
Application Temperature:	From +5°C to +45°C	
Shelf life:	Dry and fresh store, packed and sealed 18 months at least.	
Dilution:	Ready to use.	
Drying Time:	1 hour touch dry.	
Consumption:	from 0,08 – 0,1 ℓt/mq each coat.	
Packing:	0,300 ℓt - 1 ℓt – 2,5 ℓt – 5 ℓt	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility.