

## Noxide green

**NOXIDE GREEN** is a water based undercoat for iron and steel structures, based on zinc phosphate rust inhibitor. **NOXIDE GREEN** grants high protection also to steel structures exposed to heavy aggressive conditions . **NOXIDE GREEN** has a good coverage rate and hiding power with very good adhesion to duly prepared steel. It is the perfect undercoat for GREEN COAT , GREEN COAT THERMO.

**COLOURS**: white - grey - red oxide - black

SURFACE

APPLICATION: New iron steel surface: clean carefully from all grease or oil or

rust, apply one coat of primer (NOXIDE GREEN).

**Old iron surfaces**: remove all loose and flaking paints by iron brush, eliminate all rust particles. At this stage a chemical rust converter (NO RUST), can be applied on rust areas, to stop the

aggression; otherwise, use a coat of NOXIDE GREEN.

**APPLICATION:** Apply one coats of **NOXIDE GREEN**.

**Dilution:** by brush or roller max 10% water. By spray gun: (nozzle

2.5 mm) dilution max 15%.

Important: do not apply under rain or when the air

temperature is Lower than 10° C.

APPLICATION

**TOOLS** brush, roller, spray gun. Clean tools immediately after use by

warm water.



## Noxide green

>NOXIDE GREEN		N N 07
		REV 0
		DEL 19/10/2005
		SPEC. REF. N 07
TECHNICAL DATA		-
Binding Agent:	Acrylic emulsion	
Specific weight:	<b>1,48</b> kg /l ± 2%	UNI 8910
pH:	8,5÷9,5	UNI 8311
Viscosity Brookfield:	<b>20000</b> CPS a 20° C. S. 5 RPM 5 ± 10%	UNI 8490
% Solid by weight:	<b>66,5%</b> ± 2	ISTR 0007
APPLICATION DATA		
Storage temperature	From +10°C to +30°C	
Application Temperature:	From +12°C to +40°C	
Shelf life:	Dry and fresh store, packed and sealed 18 months at least.	
Dilution:	5 – 10% with water	
Drying Time:	1 hours touch dry. Recoatable after 72 hours	
Consumption:	from 6 to 8 mq/l each coat	
Packing:	0,500 ℓ - 2,5 <b>ℓ</b> - 15 ℓ	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility.

AZIENDA CON SISTEMA DI GESTIONE QUALITÀ UNI EN ISO 9001:2000 CERTIFICATO DA CERTIQUALITY **SAIF s.r.l.**VIA ACQUI, 31
15014 CANTALUPO – ALESSANDRIA - ITALY
Tel. (0131) 269207 –269208
Fax (0131) 269200