



Nuvole

NUVOLE SKY COAT is an entirely new kind of wall coverings and offers unique advantages. Although it looks delicate, **NUVOLE** has a very tough surface film coating. This elegant polychrome wall covering comes in glossy or satin finish which gives an effect that recalls the antique craftsman-ship of the past.

COLOUR: The colours of **UNO TOP** can be matched with the **NUVOLE SKY FINISH** range to produce any number of combinations to suit all tastes.

BASE PREPARATION: **Priming new plaster:** apply a coat of **SAIFSEAL DUR consolidante**, diluted 300% water.
Painted walls: ensure that existing paint is in a good condition. In case of flaking or cracking, sand wall and apply a coat of **SAIFSEAL DUR consolidante** diluted 300% water.

APPLICATION: **NUVOLE** system is applied in two times:

1) Apply two coats of **UNO TOP** in the shade selected, paced 4 - 8 hours, taking care to spread uniformly, using a wool roller. Max. dilution: 20 - 25% water. Mix the product before application.

2) Blend **NUVOLE SKY FINISH incolore** and the selected coloured dose. You can change the intensity and tonality of **NUVOLE SKY FINISH** colour by adding **SKY FINISH incolore** (colourless).

3) When the surface is completely dry, apply **NUVOLE SKY FINISH** in the selected colour with a wool roller or a paint brush.

Immediately thereafter, rotate the leatherette on the paint surface before reaching the base. Continue this rotative movement in a way that the designs are not repetitive. To prepare the leatherette, we must take two synthetic chamois leather cloths.

Place one on top the other correctly.

Now collect the centre area, in tampon for, and tie-up.

It is possible to use our special spatula which is flexible.



Nuvole

Change the direction of the spatula at all times to get varied designs and effects. To obtain a particular special effect or shaded a second coat of **NUVOLE SKY FINISH** is advisable.

NUVOLE system is not toxic and without solvents. That's why requires non special or costly application tools during application.

NUVOLE system is odourless, therefore it can be applied in hospitals, schools and in public locals.

Cleaning tools may be done by simply washing with water and a mild detergent immediately after use.

NUVOLE system is non-flammable. It has been given a high safety rating (Class 1) by I.C.T.E. - C.N.R., rapport N° 761007/1032.

NUVOLE can be easily washed.

>NUVOLE SKY FINISH		N N 11
		REV 0
		05/11/2004
		SPEC. REF. N 11
TECHNICAL DATA		
Binding agent :	acryl resin	
Specific weight:	1,03 kg /l ± 2%	UNI 8910
pH:	8,5÷9,5	UNI 8311
Viscosity Brookfield:	25000 CPS a 20° C. S. 5 RPM 5 ± 10%	UNI 8490
% Solid weight:	26,5 ± 2	ISTR 0007
APPLICATION DATA		
Storage Temperature:	From +5°C to +45°C	
Application Temperature:	From +5°C to +35°C	
Shelf life:	Dry and fresh store, packed and sealed 18 months at least.	
Dilution:	Ready to use	
Drying Time:	4 hours touch dry. Recoatable after 8-12 hours	
Consumption:	from 0,1 a 0,2 lt/sqmt according to application method.	
Packing:	5 l + pigment dose 0,320 kg -	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility.