



Pratica Super

PRATICA SUPER is water based acryl paint with very low V.O.C. content, good vapour permeability, easy to apply and good hiding power.

PRATICA SUPER is suitable for interiors walls where it is required a good quality paint at reasonable price. **PRATICA SUPER** protects the wall against moulds, thanks to a lemon scented fungicide.

PRATICA SUPER is an environmental friendly very low V.O.C. paint, in accordance with European Rules related to organic compounds emissions (Directive C.E. 2004/42 and DL 161 27-03-06)

COLOURS: White – matt, light colours available by tinting system.

SURFACE PREPARATION:

New surfaces: apply one coat of **SAIFSEAL BETON 300%** diluted 300% water.

Old surfaces: insure that all surfaces are dry, uniform and clean. Repair all defects, if any, prior to any application and then apply **SAIFSEAL DUR consolidante**, diluted 200% with water. In case the wall surface is weak and powdery, apply **SAIFSEAL DUR consolidante**. In case any presence of mould or other type of fungus growth, apply **NO MOULD** by brush or roller. When the surface is completely dry in approximately three to four hours, remove the remaining mould with a dry cotton rag.

APPLICATION:

Dilute **PRATICA SUPER** with 25-35% water.

The dilution percentage is based on the porosity and absorption of paint in the wall.

Blend thoroughly by using a flat tool.

Apply two coats of by brush, roller or spray gun. Two coats are suggested at four to six hour intervals..

Do not apply when the temperature is below +5 degrees centigrade.

PRATICA SUPER is non-toxic and contains no solvents. Therefore cleaning may be done by simply washing with water and or a mild detergent.



Pratica Super

>PRATICA SUPER		N P 11
		REV 0
		22/03/2006
		SPEC. REF. P 11
TECHNICAL DATA		
Binding agent :	Styro-Acrl Resin.	
Specific weight:	1,70 kg /l \pm 2%	UNI 8910
pH:	8,5÷9,5	UNI 8311
Viscosity Brookfield:	50000 CPS a 20° C. S. 5 RPM \pm 10%	UNI 8490
% Solid weight:	68,1% \pm 2	ISTR 0007
APPLICATION DATA		
Storage Temperature:	from +5°C to +40°C	
Application Temperature:	from da +10°C to +30°C	
Shelf life:	store in non-freezing and dry spaces. If stored in sealed drums, the materials can be stored for at least 18 months.	
Dilution:	25-35% of water depending on the absorption of wall surfaces.	
Drying Time:	One hour to be touch dry. Repainting may be performed within four to six hours.	
Consumption:	4 -5 mq/lt	
Packing:	14 l	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility