



# Stucco in pasta

**STUCCO IN PASTA**, can be applied on cement and lime based plaster to achieve a smooth surface. Usually two coats are needed to reach a good smoothness. STUCCO IN PASTA is ready to use, easy to apply, and a good base for "RIFLESSI", "MARBLECHROME" OR "CHROME COAT", "MANTOVANO", "VOLTERRA", "SENESE", etc..., provided that a coat of SAIF SEAL DUR is applied as under coat.

**APPLICATION:** Apply first coat by trowel. Let it dry. If necessary use sand paper to smooth the surface. Apply a second-coat to reach required smoothness. Max thickness allowed: mm1.

*Linea stucchi*



# Stucco in pasta

<b>&gt;STUCCO IN PASTA</b>		N S 17
		REV 0
		05/11/2004
		SPEC. S 17 REF.
<b>TECHNICAL DATA</b>		
Binding Agent:	Modified Acrylic Resin	
Specific weight:	1,95 Kg/l $\pm$ 2%	UNI 8910
pH:	8,5 $\div$ 9,5	UNI 8311
Viscosity Brookfield:	70000 CPS to 20° C. S. 2 RPM 7 $\pm$ 10%	UNI 8490
% Solid weight:	77,8% $\pm$ 2	
<b>APPLICATION DATA</b>		
Storage Temperature:	From +10°C to +30°C	
Application Temperature:	From +10°C to +45°C	
Shelf Life:	Dry and fresh store, packed and sealed 18 months at least.	
Dilution:	Ready to use.	
Drying Time:	2 hour touch dry. 10 hours to re-coat	
Consumption:	from 0,2 to 0,25 l/mq according to substrate absorption and dilution.	
Packing:	5 kg - 25 kg	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility.