



Unocoat

UNO COAT is a synthetic water based paint for interior and exterior. This technological advanced product offers a good transpirability still remaining a very washable product. Great opacity, good paintability, **UNO COAT** is filled by a very fine quartz powder, giving high resistance and non aging properties, when applied in exterior .

COLOURS: Standard white.
Full range of light colours by tintosystem.

SURFACE

PREPARATION: **New walls:** apply one coat of **SAIFSEAL ACRYL 300%** (dilution by water: 300%).
Old walls: brush all flaking and dusty old paints, clean carefully and apply one coat of **SAIFSEAL DUR** (dilution 300% by water).
Old mouldy walls : first apply one or two coats of " **NO MOULD**". After drying, take out all dusty staff and proceed with one coat of **SAIFSEAL SAN** (mould inhibitor undercoat).

APPLICATION: Dilution 20- 30% by water. Mix the product before application, let first coat dry for 4-6 hours.
Application tools: brush , roller, spray-gun.
Do not apply under +5°C. Plaster should be perfectly dry and cured. **UNO COAT** is odourless and can be apply in schools, hospitals, public places without special precautions. Clean tools immediately after application by warm water.



Unocoat

>UNO COAT		N U 01
		REV 0
		05/11/2004
		SPEC. REF. U 01
TECHNICAL DATA		
Binding agent :	Modified acryl resin	
Specific weight:	1,55 kg /l \pm 2%	UNI 8910
pH:	8,5÷9,5	UNI 8311
Viscosity Brookfield:	30000 CPS a 20° C. S. 5 RPM \pm 10%	UNI 8490
% Solid weight:	65,1% \pm 2	ISTR 0007
APPLICATION DATA		
Storage Temperature:	From +5°C to +45°C	
Application Temperature:	From +5°C to +40°C	
Shelf life:	Dry and fresh store, packed and sealed 18 months at least.	
Dilution:	20-30% water, according to substrate absorption .	
Drying Time:	1 hours touch dry. Recoatable after 4-6 hours.	
Consumption:	6 - 8 lt/mq	
Packing:	2,5 lt – 15 lt.	